7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-048

Revision:

AllnGaP LED DICE

Part NO.: AOC-112GLA Series

Features


- Green Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-112GLA series is a green color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size: 10.8mil×10.8mil±0.5mil Bonding Pad: \$\phi4.0\text{mil}\pm0.4\text{mil}\$ Chip Thickness: 6.5mil±1.0mil

Specification and Optical Characteristics

-						
Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	\mathbf{V}_{F}	I _F =20mA	1.70 -		2.20	V
Reverse Current	Ir	V _R =-5V	-	-	1.0	μ A
Dominant Wavelength	λd	I _F =20mA	550	-	566	nm
Max. Junction Temperature	T_{max}	-	≦ 115		$^{\circ}\!\mathbb{C}$	
Max. DC forward current	I_{f}	Ta = 25°C	≤ 50		mA	
Max. pulse forward current	$ m I_{fm}$	Ta = 25°C		≤ 100		mA
(Pulse width 0.1 msec, frequency=1 kHz.)	1 fm	14 25 0	≡ 100			111/1
Storage temperature	T_{stg}	Chip on tape	0 ~ 40		$^{\circ}\! \mathbb{C}$	
		Only chip	- 40 ∼ 80			

Available Dominate Wavelength and Iv Matrix

Minimum Intensity (@20mA)	IV ≥ 5mcd	IV ≥ 10mcd	IV ≥ 15mcd	IV ≥ 20mcd	IV ≥ 30mcd
Grade	X1	X2	X3	A	В

Not:

- All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.
- Above contents are subject to change without notice.

 Special requests are also welcome, please contact AOC's sale representative for any request.

1/1 http://www.aocepi.com 4-1O-QE00-021-001 Rev.00