7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-055

Revision: 2

AllnGaP LED DICE

Part NO.: AOC-112GLC Series

Features


- Green Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-112GLC series is a green color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size: 10.8mil×10.8mil±0.5mil Bonding Pad: \phi3.8mil±0.3mil Chip Thickness: 6.5mil±1.0mil

N-electrode

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	\mathbf{V}_{F}	$I_F=20mA$	1.70	-	2.20	V
Reverse Current	Ir	V _R =-5V	-	-	1.0	μΑ
Dominant Wavelength	λd	I _F =20mA	550	-	566	nm
Max. Junction Temperature	T_{max}	-	≤ 115			$^{\circ}\!\mathbb{C}$
Max. DC forward current	I_{f}	$Ta = 25^{\circ}C$	≤ 50			mA
Max. pulse forward current	I_{fm} $Ta = 25^{\circ}C$ ≤ 100			mA		
(Pulse width 0.1 msec, frequency=1 kHz.)	1 fm	14 25 0	≡ 100			ША
Storage temperature	$T_{ m stg}$	Chip on tape	0 ~ 40			$^{\circ}\!\mathrm{C}$
Storage temperature		Only chip	- 40 ~ 80			

Available Dominate Wavelength and Iv Matrix

Part No.	Wavelength Range	≥ 5 mcd	≥ 10 mcd	≥ 15 mcd	≥ 20 mcd	≥ 30 mcd	≥ 40 mcd	≥ 50 mcd
112 GLC	550 ~ 566 nm	-	X2	Х3	A	В	-	-

Not:

- 1. All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.
- B. Above contents are subject to change without notice.
- 4. Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00