7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-003

Revision: 2

AllnGaP LED DICE

Part NO.: AOC-1080xA Series


Features


- Orange Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-108OxA series is a orange color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size: 6.6mil*6.6mil±0.5mil Bonding Pad: \phi4.0mil±0.4mil Chip Thickness: 6.5mil±1.0mil

N-electrode

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min Typ		Max	Unit
Forward Voltage	V_{F}	I _F =20mA	1.70 - 2.		2.30	V
Reverse Current	Ir	V _R =-5V			1.0	μ A
Dominant Wavelength	λd	I _F =20mA	600	-	620	nm
Max. Junction Temperature	T_{max}	-	≦ 115			$^{\circ}\!\mathbb{C}$
Max. DC forward current	$ m I_f$	Ta = 25°C	≤ 20			mA
Max. pulse forward current	$ m I_{fm}$	Ta = 25°C	≦ 40			mA
(Pulse width 0.1 msec, frequency=1 kHz.)	11m	1 u 25 0				
Storage temperature	$T_{ m stg}$	Chip on tape $0 \sim 40$			$^{\circ}\mathrm{C}$	
		Only chip	-40 ~ 80			

Available Dominate Wavelength and Iv Matrix

Minimum Intensity	IV≥	IV≥						
(@20mA)	40mcd	50mcd	60mcd	70mcd	80mcd	90mcd	100mcd	110mcd
Grade	С	D	Е	F	G	Н	I	J

Not:

- All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.
- Above contents are subject to change without notice.
- Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00