

Cat No.: Revision:

7-1S-1000-018 3

AllnGaP LED DICE

Part NO.: AOC-1090xA Series


Features


- Orange Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-109OxA series is a orange color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size : 7.8mil×7.8mil±0.5mil Bonding Pad : \phi4.0mil±0.4mil Chip Thickness : 6.5mil±1.0mil

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	\mathbf{V}_{F}	I _F =20mA	1.70	-	2.30	V
Reverse Current	Ir	VR=-5V	-	-	1.0	μA
Dominant Wavelength	λd	I _F =20mA	600	-	620	nm
Max. Junction Temperature	T _{max}	-	≦ 115			°C
Max. DC forward current	I_{f}	$Ta = 25^{\circ}C$	\leq 30			mA
Max. pulse forward current (Pulse width 0.1 msec, frequency=1 kHz.)	I_{fm}	$Ta = 25^{\circ}C$	≤ 60			mA
Storage temperature	T _{stg}	Chip on tape	$0 \sim 40$			°C
		Only chip		C		

Available Dominate Wavelength and Iv Matrix

Part No.	Wavelength	≥ 50	≥60	≥ 70	≥ 80	≥90	≥ 100	≥110	≥ 120	≥130
	Range	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd
109 OSA	$600 \sim 610 \text{ nm}$	D	Е	F	G	Н	Ι	J	K	-
109 OLA	$610\sim 620 \ nm$	D	Е	F	G	Н	Ι	-	-	-

Not:

1. All measurements are done with AOC's standard testing equipment.

2. Luminance intensity is measured on bare chip.

3. Above contents are subject to change without notice.

Special requests are also welcome, please contact AOC's sale representative for any request.