7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-042

Revision: 3

AllnGaP LED DICE

Part NO.: AOC-112RxA Series

Features


- Red Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-112RxA series is a red color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





N-electrode

Chip Size: 10.8mil×10.8mil±0.5mil Bonding Pad: \phi4.0mil±0.4mil Chip Thickness: 6.5mil±1.0mil

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	V_{F}	$I_F=20mA$	1.70 -		2.20	V
Reverse Current	Ir	V _R =-5V	-	-	1.0	μ A
Dominant Wavelength	λd	I _F =20mA	616	-	645	nm
Max. Junction Temperature	T_{max}	-	≦ 115			$^{\circ}\!\mathbb{C}$
Max. DC forward current	I_{f}	Ta = 25°C	≤ 50			mA
Max. pulse forward current	$ m I_{fm}$	Ta = 25°C	≦ 100			mA
(Pulse width 0.1 msec, frequency=1 kHz.)	11m	14 25 0				
Storage temperature	T_{stg}	Chip on tape	0 ~ 40			\cdot $^{\circ}$
Storage temperature		Only chip				

Available Dominate Wavelength and Iv Matrix

	Part No.	Wavelength	≥ 30	≥ 40	≥ 50	≥ 60	≥ 70	≥ 80	≥ 90	≥ 100	≥ 110
		Range	mcd	mcd							
	112 RSA	616 ~ 625 nm	-	-	D	Е	F	G	Н	I	J
	112 RMA	$620\sim630\;\text{nm}$	-	С	D	Е	F	G	Н	-	-
	112 RLA	625 ~ 635 nm	В	С	D	Е	F	-	-	-	-

Not:

- 1. All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.
- 3. Above contents are subject to change without notice.
- 4. Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00