7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-023

Revision: 3

AllnGaP LED DICE

Part NO.: AOC-109YGxA Series


Features


- Yellow green Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-109YGxA series is a yellow green color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size: 7.8mil×7.8mil±0.5mil Bonding Pad: \phi4.0mil±0.4mil Chip Thickness: 6.5mil±1.0mil

N-electrode

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	V_{F}	$I_F=20mA$	1.70	-	2.30	V
Reverse Current	Ir	V _R =-5V	1	1	1.0	$\mu \mathbf{A}$
Dominant Wavelength	λd	I _F =20mA	567	-	577	nm
Max. Junction Temperature	T_{max}	-		≦ 115		$^{\circ}\!\mathbb{C}$
Max. DC forward current	$ m I_f$	$Ta = 25^{\circ}C$		≦ 30		mA
Max. pulse forward current	$ m I_{fm}$	Ta = 25°C	≦ 60			mA
(Pulse width 0.1 msec, frequency=1 kHz.)		1a – 25 C				
Storage temperature	T_{stg}	Chip on tape	0 ~ 40			$^{\circ}\! \mathbb{C}$
		Only chip	- 40 ~ 80			

Available Dominate Wavelength and Iv Matrix

Part No.	Wavelength Range	≥ 10 mcd	≥ 20 mcd	≥ 30 mcd	≥ 40 mcd	≥ 50 mcd	≥ 60 mcd	≥ 70 mcd
109 YGSA	567 ~ 573 nm	-	-	В	С	D	-	-
109 YGLA	571 ~ 577 nm	-	-	-	С	D	Е	-

Not:

- 1. All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.
- 3. Above contents are subject to change without notice.
- Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00