7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-050

Revision: 2

# AllnGaP LED DICE

## Part NO.: AOC-109YGxC Series


#### **Features**


- Yellow green Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

#### **Description**

AOC-109YGxC series is a yellow green color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

### **Chip Dimensions**





Chip Size: 7.7mil×7.7mil±0.5mil Bonding Pad: \phi3.8mil±0.3mil Chip Thickness: 6.5mil±1.0mil

N-electrode

#### **Specification and Optical Characteristics**

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	$V_{\mathrm{F}}$	I <sub>F</sub> =20mA	1.70	1.70 -		V
Reverse Current	Ir	V <sub>R</sub> =-5V	1	-	1.0	$\mu$ A
Dominant Wavelength	λd	I <sub>F</sub> =20mA	567	-	577	nm
Max. Junction Temperature	$T_{\text{max}}$	-		$^{\circ}\!\mathbb{C}$		
Max. DC forward current	$I_{\mathrm{f}}$	Ta = 25°C		mA		
Max. pulse forward current (Pulse width 0.1 msec, frequency=1 kHz.)	$ m I_{fm}$	Ta = 25°C	≤ 60			mA
Storage temperature	$T_{\mathrm{stg}}$	Chip on tape	0 ~ 40			$^{\circ}$ C
		Only chip				

# **Available Dominate Wavelength and Iv Matrix**

Part No.	Wavelength	≥ 30	≥ 40	≥ 50	≥ 60	≥ 70	≥ 80	≥ 90	≥100	≥ 110	≥ 120	≥ 130
	Range	mcd	mcd	mcd								
109 YGSC	567 ~ 573 nm	-	-	D	Е	F	G	Н	I	J	-	-
109 YGLC	571 ~ 577 nm	-	-	-	-	-	-	-	-	-	-	-

#### Not:

- 1. All measurements are done with AOC's standard testing equipment.
- 2. Luminance intensity is measured on bare chip.
- 3. Above contents are subject to change without notice.
- 4. Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00