Cat No.: Revision:

AllnGaP LED DICE

Part NO.: AOC-108YxA-4mil Series


Features


- Yellow Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-108YxA-4mil series is a yellow color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size : 6.3mil×6.3mil±0.5mil Bonding Pad : ϕ 4.0mil±0.4mil Chip Thickness : 4.0mil±1.0mil

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	V_{F}	I _F =20mA	1.70 -		2.30	V
Reverse Current	Ir	$V_R=-5V$			1.0	μA
Dominant Wavelength	λd	I _F =20mA	A 582 -		598	nm
Max. Junction Temperature	T _{max}	-	\leq 115			°C
Max. DC forward current	I_{f}	$Ta = 25^{\circ}C$	≤ 20			mA
Max. pulse forward current	I_{fm}	$Ta = 25^{\circ}C$	\leq 40			mA
(Pulse width 0.1 msec, frequency=1 kHz.)	1 fm	1a 25 C				
Storage temperature	T _{stg}	Chip on tape	0~40			°C
		Only chip	$-40 \sim 80$			

Available Dominate Wavelength and Iv Matrix

Minimum Intensity	IV≥	IV ≥						
(@20mA)	20mcd	30mcd	40mcd	50mcd	60mcd	70mcd	80mcd	90mcd
Grade	А	В	С	D	Е	F	G	Н

Not:

All measurements are done with AOC's standard testing equipment.

2. Luminance intensity is measured on bare chip. Above contents are subject to change without notice.

3. Special requests are also welcome, please contact AOC's sale representative for any request. YxA represents anyone of YSA(582nm~592nm) and YLA(590nm~598nm). 4. 5.