7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-032

Revision:

AllnGaP LED DICE

Part NO.: AOC-109YxA-4mil Series


Features


- Yellow Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-109YxA-4mil series is a yellow color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size: 7.7mil×7.7mil±0.5mil Bonding Pad: \$\phi4.0\text{mil}\pm0.4\text{mil}\$ Chip Thickness: 4.0mil±1.0mil

N-electrode

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	V_{F}	I _F =20mA	1.70 -		2.30	V
Reverse Current	Ir	V _R =-5V	1	-	1.0	μ A
Dominant Wavelength	λd	I _F =20mA	582	-	598	nm
Max. Junction Temperature	T_{max}	-	≤ 115≤ 30			$^{\circ}\!\mathbb{C}$
Max. DC forward current	${ m I_f}$	$Ta = 25^{\circ}C$				mA
Max. pulse forward current (Pulse width 0.1 msec, frequency=1 kHz.)	${ m I}_{ m fm}$	Ta = 25°C		mA		
	T_{stg}	Chip on tape	0 ~ 40			$^{\circ}$
Storage temperature		Only chip				

Available Dominate Wavelength and Iv Matrix

	Part No.	Wavelength	≥ 40	≥ 50	≥ 60	≥ 70	≥80	≥ 90	≥ 100	≥ 110	≥ 120	≥ 130
	rait No.	Range	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd
	YSA-4	582 ~ 592 nm	-	D	Е	F	G	Н	I	J	-	-
	YLA-4	590 ~ 598 nm	-	D	Е	F	G	Н	I	J	K	-

Not:

- All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.
- Above contents are subject to change without notice.

 Special requests are also welcome, please contact AOC's sale representative for any request.

1/1 http://www.aocepi.com 4-1O-QE00-021-001 Rev.00