7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-075

Revision: 0

AllnGaP LED DICE

Part NO.: AOC-109YxP Series


Features


- Yellow Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-109YxP series is a yellow color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed for high brightness automobile, display, and consumer electronic applications.

Chip Dimensions





Chip Size: 7.7mil×7.7mil±0.5mil Mask Size: 9.0mil×9.0mil

Bonding Pad : \$\phi 3.8\text{mil}\pmu 0.3\text{mil}\$ Chip Thickness : 6.5\text{mil}\pmu 1.0\text{mil}\$

Specification and Optical Characteristics

•						
Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	V_{F}	I _F =20mA	1.70	-	2.30	V
Reverse Current	Ir	V _R =-5V	-	-	1.0	μ A
Dominant Wavelength	λd	I _F =20mA	585	-	595	nm
Max. DC forward current	I_{f}	Ta = 25°C	≤ 30 ≤ 60 ≤ 120			mA
Max. pulse forward current (Pulse width 0.1 msec, frequency=1 kHz.)	I_{fm}	Ta = 25°C				mA
Junction temperature	T _j					$^{\circ}\!\mathbb{C}$
Staraga tamparatura	$T_{ ext{stg}}$	Chip on tape	0 ~ 40		$^{\circ}\!\mathbb{C}$	
Storage temperature		Only chip	-40 ~ 120			$^{\circ}$ C

Available Dominate Wavelength and Iv Matrix

				_							
	Part No.	Wavelength	≥ 70	≥ 80	≥ 90	≥ 100	≥ 110	≥ 120	≥ 130	≥ 140	≥ 150
	rait No.	Range	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd	mcd
	109 YxP	585 ~ 595 nm	F	G	Н	I	J	K	L	M	N

Not:

- 1. All measurements are done with AOC's standard testing equipment.
- 2. Luminance intensity is measured on bare chip.
- Above contents are subject to change without notice.
- 4. Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00