7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan (R.O.C) 335

Cat No.: 7-1S-1000-053

Revision: 2

AllnGaP LED DICE

Part NO.: AOC-112YxC Series

Features


- Yellow Color Emission
- Excellent performance and high efficiency
- Great reliability even in harsh environment

Description

AOC-112YxC series is a yellow color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency and therefore a greater light intensity. This device is designed to suit the growing demand in the compact size electronic goods.

Chip Dimensions





Chip Size: 10.8mil×10.8mil±0.5mil Bonding Pad: \phi3.8mil±0.3mil Chip Thickness: 6.5mil±1.0mil

N-electrode

Specification and Optical Characteristics

Measuring Item	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	\mathbf{V}_{F}	$I_F=20mA$	1.70 - 2.20			V
Reverse Current	Ir	V _R =-5V	-	-	1.0	μ A
Dominant Wavelength	λd	I _F =20mA	582	-	598	nm
Max. Junction Temperature	T_{max}	-	≦ 115			$^{\circ}\!\mathbb{C}$
Max. DC forward current	I_{f}	Ta = 25°C	≤ 50			mA
Max. pulse forward current	$ m I_{fm}$	Ta = 25°C	≦ 100			mA
(Pulse width 0.1 msec, frequency=1 kHz.)	1fm	14 25 0				
Storage temperature	$T_{ m stg}$	Chip on tape	0 ~ 40			$^{\circ}\mathbb{C}$
		Only chip	- 40 ~ 80			

Available Dominate Wavelength and Iv Matrix

Part No.	Wavelength	≥ 130	≥ 140	≥ 150	≥ 160	≥ 170	≥ 180	≥ 190	≥ 200	≥ 210	≥ 220	≥ 230
	Range	mcd										
112YSC	582~592 nm	-	-	-	О	P	Q	R	S	T	-	-
112YLC	590~598 nm	-	-	-	-	-	-	-	-	-	-	-

Not:

- 1. All measurements are done with AOC's standard testing equipment.
- 2. Luminance intensity is measured on bare chip.
- Above contents are subject to change without notice.
- 4. Special requests are also welcome, please contact AOC's sale representative for any request.

http://www.aocepi.com 1/1 4-10-QE00-021-001 Rev.00